

CH-HP75UIMZM														
Max. Heating Capacity (kW)														
Water outlet(°C)	-25	-20	-15	-10	-7	-5	2	7	10	15	20	25	35	43
35	32.50	38.23	42.96	50.73	52.49	54.33	67.19	75.00	88.39	95.11	97.98	100.10	113.68	122.66
45	32.18	37.86	42.54	49.26	49.87	51.61	64.20	74.86	86.88	94.25	96.96	97.10	100.53	102.03
50	32.68	37.45	42.00	48.01	48.22	51.90	62.70	74.80	84.12	92.87	94.98	95.86	100.20	91.71
55	24.12	37.00	41.52	46.80	47.61	50.34	61.13	74.73	76.20	90.91	90.99	94.62	88.56	86.55
60	19.84	36.53	40.05	45.61	46.12	49.80	59.61	65.61	67.27	83.91	83.60	84.27	76.92	64.87
65		32.83	36.88	40.98	43.23	44.75	48.75	56.49	57.32	65.60	72.82	73.92	65.27	54.03
70			32.73	36.37	38.37	39.71	47.29	54.80	48.01	54.32	62.04	63.58	53.63	32.34
Power Input (kW)														
Water outlet(°C)	-25	-20	-15	-10	-7	-5	2	7	10	15	20	25	35	43
35	18.46	19.03	19.62	21.28	22.09	22.32	23.12	21.48	21.59	22.67	22.83	23.45	22.16	22.63
45	19.69	20.30	20.93	22.71	23.02	23.26	24.62	22.92	21.60	25.51	25.51	25.36	21.77	22.00
50	21.01	21.66	22.33	24.53	24.90	23.01	27.60	24.46	30.72	31.19	30.86	29.29	23.69	20.73
55	20.23	24.78	25.55	26.42	26.78	24.55	29.45	29.09	29.19	30.17	29.90	31.38	24.01	20.21
60	19.67	26.44	27.26	28.19	28.66	26.20	29.14	28.79	27.66	29.15	28.94	29.06	24.32	15.43
65		26.00	26.80	27.72	28.18	25.76	26.22	25.94	25.85	24.96	24.96	26.74	24.63	13.49
70			28.60	29.58	30.07	27.48	27.97	24.36	24.45	25.37	25.37	24.43	24.95	11.92
COP(kW/kW)														
Water outlet(°C)	-25	-20	-15	-10	-7	-5	2	7	10	15	20	25	35	43
35	1.76	2.01	2.19	2.35	2.38	2.43	2.91	3.49	4.09	4.20	4.29	4.27	5.13	5.42
45	1.63	1.86	2.03	2.16	2.17	2.22	2.61	3.27	4.02	3.69	3.80	3.83	4.62	4.64
50	1.56	1.73	1.88	1.96	1.94	2.26	2.27	3.06	2.74	2.98	3.08	3.27	4.23	4.42
55	1.19	1.49	1.63	1.77	1.78	2.05	2.08	2.57	2.61	3.01	3.04	3.02	3.69	4.28
60	1.01	1.38	1.47	1.62	1.61	1.90	2.05	2.28	2.43	2.88	2.89	2.90	3.16	4.20
65		1.26	1.38	1.48	1.53	1.74	1.86	2.18	2.22	2.63	2.92	2.76	2.65	4.00
70			1.14	1.23	1.28	1.44	1.69	2.25	1.96	2.14	2.45	2.60	2.15	

